

Specific energy consumption (SEC) cold	[ kWh/m <sup>2</sup> a ]	-75.7
Specific energy consumption (SEC) average	[ kWh/m <sup>2</sup> a ]	-37
Specific energy consumption (SEC) warm	[ kWh/m <sup>2</sup> a ]	-12.2
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		recuperative
Thermal efficiency of heat recovery	[ % ]	90.4
Maximum flow rate	[ m <sup>3</sup> /h ]	182
Electric power input of the fan drive at maximum flow rate	[ W ]	82
Sound power level (Lwa)	[ dB(A) ]	51
Reference flow	[ m <sup>3</sup> /s ]	0.035
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m <sup>3</sup> /h) ]	0.31
Control factor and control typology		0.95
Declared maximum internal leakage rates	[ % ]	1.2
Declared maximum external leakage rates	[ % ]	1.2
Possition and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	391
AEC cold	[ kWh ]	928
AEC warm	[ kWh ]	346
AHS Average	[ kWh/a ]	4610
AHS Cold	[ kWh/a ]	9018
AHS Warm	[ kWh/a ]	2085
ErP Compliance		2018
Internet address for disassembly instructions		<a href="http://www.salda.it">www.salda.it</a>

